

**MULTI-CURRENT SWITCHING**


**Model Number  
AC-150C3.0UV-TS**

Input Voltage: 120-277V  
Input Frequency: 50/60Hz  
Side Mount/Leads

**ELECTRICAL SPECIFICATIONS:**

Output Power Max.	Input Power	Input Current	Minimum PF (full load)	Max. THD (full load)	Output Voltage	Output Current	T case Max.	Minimum Starting Temp.	Efficiency Up To	IP Rating
150W	172W	1.45A @ 120V 0.64A @ 277V	>0.95	<20%	30-50V	3000mA±5%	90° C	-40° C	87%	64
100W	111W	0.93A @ 120V 0.4A @ 277V	>0.95	<20%	30-50V	2000mA±5%	90° C	-40° C	86%	64
50W	60W	0.5A @ 120V 0.22A @ 277V	>0.95	<20%	30-50V	1000mA±5%	90° C	-40° C	85%	64

**WIRING:**



**Lead Lengths**

Black	5.9"	Blue	5.9"
White	5.9"	Red	5.9"

**PHYSICAL:**



**Dimensions**

Length	9.5"
Width	2.64"
Height	1.6"
Mounting Length	8.9"

**SAFETY & PERFORMANCE:**

- UL Recognized US
- UL Outdoor Type I
- Class A sound rating
- No PCBs
- Open/Short Circuit Protection
- LED driver has a life expectancy of 50,000 hours at Tcase of ≤75°C
- LED driver has a life expectancy of 100,000 hours at Tcase of ≤65°C
- Warranty: 5 years based on max case temp of 90°C\*
- Input/Output Isolation
- FCC Title 47 CFR Part 15
- Surge Protection (3 Kv)

**INSTALLATION:**

- LED drivers shall be installed inside UL approved electrical enclosures
- 18 AWG 600V/105C tinned strand copper lead-wires are required for installation
- Max Remote installation distance is 18 ft
- LED driver cases shall be grounded



\*AC Electronics/AC LED Power Designs warrants to the purchaser that each LED Driver will be free from defects in material or workmanship for a period of 5 years when operated at max case temp of up to <75°C; 3 years from date of manufacture when operated at a max case temp of up to 90°C when properly installed and under normal conditions of use. See [aceleds.com](http://aceleds.com) for complete warranty policy.

3401 Avenue D, Arlington, TX 76011 • 800-375-6355 • [www.aceleds.com](http://www.aceleds.com)

Data is based upon tests performed by AC Electronics in a controlled environment and representative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice. All specifications are nominal unless otherwise noted.

