

File E328847  
Project 4786599993

December 5, 2014

REPORT

ON

COMPONENT - DRIVERS FOR LIGHT-EMITTING-DIODE ARRAYS, MODULES AND CONTROLLERS

ANTRON ELECTRONICS CO LTD  
TAINAN, TAIWAN

Copyright © 2014 UL LLC

UL LLC authorizes the above named company to reproduce this Report either in its entirety or the portion of this Report consisting of the Cover Page up to (but not including) the Construction Details descriptive pages.

## DESCRIPTION

## PRODUCT COVERED:

USR, CNR - Component LED Drivers for Light-emitting-diode Arrays, Modules and Controllers, Suitable for Damp Location, Models **AC-25CD1.25BPME**, AC25CD1.25BPBME, AC-25CD1.25BPMV, AC25CD1.25BPBMV, AC-40CD1.4APSC, AC-40CD1.4APKV, AC-40CD1.4APBKV, AC-40CD1.4APMZ, AC-25CD700ATM, AC25CD1.25APBME, AC-25CD1.25APME, AC-25CD1.25APMV, AC-40CD1.4BPKV, AC-40CD1.4BPBKV, AC-40CD1.4BPBMZ, AC-60CD1.4APPU, AC-98CD2.1APMX, AC-98CD2.1APBMX, AC-98CD2.1APMY (where "x" may be any alphanumeric character, "-" or blank).

Note: USR - United States Standard, Recognized  
CNR - Canadian Standard, Recognized

## ELECTRICAL RATINGS:

Model No.	Input Voltage (Vac)	Input Freq (HZ)	Input Current (A)	Max Output Voltage (Vdc)	Max Output Current (A)	Max Output Watt (W)	Driver Type
AC-25CD700ATM AC25CD1.25APBME AC-25CD1.25APME AC-25CD1.25APMV	120-277	50/60	0.27- 0.11	55	1.25	25	TL
AC-40CD1.4APSC AC-40CD1.4APKV AC-40CD1.4APBKV AC-40CD1.4APMZ	120-277	50/60	0.4- 0.18	55	1.4	40	TL
<b>AC-25CD1.25BPME</b> AC25CD1.25BPBME AC-25CD1.25BPMV AC25CD1.25BPBMV	347	50/60	0.097	55	1.25	25	TL
AC-40CD1.4BPKV AC-40CD1.4BPBKV AC-40CD1.4BPBMZ	347	50/60	0.143	55	1.4	40	TL
AC-60CD1.4APPU	<b>120-277</b>	<b>50/60</b>	<b>0.60- 0.26</b>	<b>59</b>	<b>1.4</b>	<b>60</b>	<b>TL</b>
AC-98CD2.1APMX AC-98CD2.1APBMX AC-98CD2.1APMY	<b>120-277</b>	<b>50/60</b>	<b>0.94- 0.41</b>	<b>58</b>	<b>2.1</b>	<b>98</b>	<b>TL</b>

## TECHNICAL CONSIDERATIONS (NOT FOR FIELD REPRESENTATIVE'S USE):

Special Considerations - The following items are considerations that were used when evaluating this product.

Use - For use only in (or with) complete equipment where the acceptability of the combination is determined by UL LLC.

USR - Indicates investigation to the United States requirements for the Light Emitting Diode Equipment for Use in Lighting Products, UL 8750, 1st Edition; and the Standard for Class 2 Power Units, UL 1310, 6th Edition.

CNR - Indicates investigation to the Canadian Standard for Power Supplies with Extra-Low-Voltage Class 2 Outputs, CAN/CSA-C22.2 No. 223-M91, 2nd Edition; and the Canadian Standard for Light emitting diode (LED)

equipment for lighting applications, CAN/CSA-C22.2 No. 250.13-14, 2nd Edition.

CN - Either the Canadian Standards Association Certification or Component Acceptance Mark or the UL Listing or UL Recognition Mark for Canada.

\* PWB spacings have been evaluated in accordance with an Overvoltage Category II and Pollution Degree 1 (potted enclosure) per Clause 7.8.3 and Table 7.4 of UL 8750 with live parts to enclosure spacings evaluated per

**Table 7.6 and CSA C22.2 No. 250.13-12, Clause 8.7.3, Table 5 with live parts to enclosure spacings evaluated per Table 6.**

The descriptions of certain components in this Report contain the notation "CN". "CN" indicates that the component has been evaluated to Canadian requirements. Whenever "CN" appears, the Field Representative shall confirm that the component has a CSA Certification Mark or an equivalent identifier or a Canadian UL Listing or Recognition Mark if the product described in this Report bears the UL's Classification Mark for Canada.

Condition of Acceptability - When installed in the end use equipment, the following are among the considerations to be made:

1. The LED drivers have been evaluated using resistive load resulting in output currents, which are equal to each output rated current. The need for repeating tests related to heating and the Isolated Class 2 output shall be considered in the end product if the loads used result in the current exceeding the rated marked current.
2. The LED drivers have been tested at 50°C ambient. Acceptable operation at a higher temperature should be determined in end products.
3. The units are intended for factory installation only.
4. Models AC-25CD700ATM, AC25CD1.25APBME, AC-25CD1.25APME, AC-25CD1.25APMV, AC-40CD1.4APSC, AC-40CD1.4APKV, AC-40CD1.4APBKV, AC-40CD1.4APMZ, **AC-25CD1.25BPME**, AC25CD1.25BPBME, AC-25CD1.25BPMV, AC25CD1.25BPBMV, AC-40CD1.4BPKV, AC-40CD1.4BPBKV, AC-40CD1.4BPBMZ  
Are intended for using in damp location, other uses shall be considered in the end products.
5. These LED drivers are provided with Class 2 output complies with UL 1310 and CSA C22.2, No.223.
6. These LED drivers are provided with isolated output.
7. The suitability of enclosure shall be determined in the end-use product and comply with the enclosure, mounting, spacing, casualty, and segregation requirements of the end product application.
8. The grounding wires are to be used for bonding in the end product only (not for supply ground connection).
9. The following models were evaluated per the Temperature Limited (Type TL) requirements per Supplement SB of UL8750 and the measured Tref max temperature associated with the measured Tc and Ta values are as follows:

Model	Measured Tref Value (°C)	Tref max Value (°C)
AC-25CD700ATM AC25CD1.25APBME AC-25CD1.25APME	58.2	90

AC-25CD1.25APMV AC-40CD1.4APSC AC-40CD1.4APKV AC-40CD1.4APBKV AC-40CD1.4APMZ		
<b>AC-25CD1.25BPME</b> AC25CD1.25BPBME AC-25CD1.25BPMV AC25CD1.25BPBMV AC-40CD1.4BPKV AC-40CD1.4BPBKV AC-40CD1.4BPBMZ	48.5	90
AC-60CD1.4APPU	<b>53.0</b>	<b>90</b>
AC-98CD2.1APMX AC-98CD2.1APBMX AC-98CD2.1APMY	<b>55.4</b>	<b>90</b>

10. All units utilize a Class F insulation system for the isolation transformer (T2).

The maximum recorded temperatures for Model AC-40CD1.4BPKV, AC-40CD1.4BPBKV, AC-40CD1.4BPBMZ (represents Model AC-25CD700ATM, AC25CD1.25APBME, AC-25CD1.25APME, AC-25CD1.25APMV) were as follows when tested at an ambient of 50°C.

Transformer T2 Coil: 102.0°C  
Tc Point on Case above T1: 68.2°C

The maximum recorded temperatures for Model **AC-25CD1.25BPME**, AC25CD1.25BPBME, AC-25CD1.25BPMV, AC25CD1.25BPBMV (represents Model **AC-25CD1.25BPME**, AC25CD1.25BPBME, AC-25CD1.25BPMV, AC25CD1.25BPBMV) were as follows when tested at an ambient of 50°C.

Transformer T2 Coil: 77.8°C  
Tc Point on Case above T2: 58.5°C

**The maximum recorded temperatures for Model AC-60CD1.4APPU  
Were as follows when tested at an ambient of 40°C.**

**Transformer T2 Coil: 71.7°C  
Tc Point on Case above T2: 66.4°C**

**The maximum recorded temperatures for Model AC-98CD2.1APMX, AC-98CD2.1APBMX  
AC-98CD2.1APMY were as follows when tested at an ambient of 40°C.**

**Transformer T2 Coil: 82.5°C  
Tc Point on Case above T2: 80.0°C**

11. These products were tested while connected to a 20A branch circuit.
12. The Leakage current test was only conducted between exposed conductive surface and the grounded pole of the supply circuit.
13. The enclosure is required to be grounded in the end-use application.
14. Models AC-25CD700ATM, AC25CD1.25APBME, AC-25CD1.25APME, AC-25CD1.25APMV, AC-40CD1.4APSC, AC-40CD1.4APKV, AC-40CD1.4APBKV, AC-40CD1.4APMZ, **AC-25CD1.25BPME**, AC25CD1.25BPBME, AC-25CD1.25BPMV, AC25CD1.25BPBMV, AC-40CD1.4BPKV, AC-40CD1.4BPBKV, AC-40CD1.4BPBMZ, AC-60CD1.4APPU, AC-98CD2.1APMX, AC-98CD2.1APBMX, AC-98CD2.1APMY had a measured maximum output more than 42.4 Vdc but less than 60 Vdc on no load condition. See tabulation for details. These outputs comply with the definition of Class 2 per the Canadian Electrical Code. These outputs cannot be accessible based on maximum voltage restrictions for Class 2 circuits in the Canadian Electrical Code. These products have accessible output terminals. The output terminals of the end products should be evaluated to confirm compliance with this accessibility requirement, either based on output terminal design or based on manufacturer specifications for their use in restricted access areas only.

