



**PROGRAMMABLE,  
DIGITAL, WIDE-RANGE  
ADJUSTABLE CURRENT & DIMMING  
TYPE TL RATED**

Constant Current LED Driver


**Model Number**  
**AC-40CDI.4BPKV**  
**AC-40CDI.4BPMZ**  
**AC-40CDI.4BPKV**  
**AC-40CDI.4BPKV**

Input Voltage: 347V  
Input Frequency: 50/60Hz  
Side & Bottom Mount/Leads Options  
< 1 Sec. Start time/(Starting with batch code AKT.48)  
**Dim-to-Off @ Max Current**

**ELECTRICAL SPECIFICATIONS:**

Output Power Max	Input Power	Input Current	Min PF (full load)	Max THD (full load)	Output Voltage	Output Current	T case Max	Min. Starting Temp	IP Rating	Efficiency Up To	Dimming Protocol	Dimming Range
40W	47W	0.143@347V	>95	<20	15-55V	400mA - 1400mA	90°C	-40°C	64	85%	0 to 10V	1 to 100%


**WIRING:**



**Lead Lengths**

Black	5.9"	Blue	5.9"	Purple	5.9"
White	5.9"	Red	5.9"	Gray	5.9"

**PHYSICAL:**



Model	Length	Width	Height	Mounting
AC-40CDI.4BPKV	5.23"	2.48"	1.18"	4.84"
AC-40CDI.4BPMZ	6.22"	1.73"	1.22"	5.86"
AC-40CDI.4BPKV	4.56"	2.48"	1.18"	xxxx
AC-40CDI.4BPKV	6.22"	1.73"	1.22"	5.86"

**SAFETY:**

- UL and cUL Recognized
- UL Outdoor Type I
- Class A sound rating
- Overload Protection
- Open/Short Circuit Protection
- LED driver has a life expectancy of 50,000 hours at Tcase of ≤75°C
- LED driver has a life expectancy of 100,000 hours at Tcase of ≤65°C
- Warranty: 5 yrs based on max case temp of <75°C; 3 yrs based on max case temp of 90°C\*
- Input/Output Isolation
- FCC Title 47 CFR Part 15
- Surge Protection (3 Kv)

Tref Max Value (°C)	Tc/Tref Value (°C)	Ta Value (°C)
90	48.5	40

The LED Driver Type TL Program is intended to assist you in gaining greater market access for your LED drivers. This service is also intended to assist end-product LED Luminaire manufacturers improve their speed-to-market by making it easy to source a compliant LED Driver.

**INSTALLATION:**

- Max Remote installation distance is 18 ft
- LED driver cases should be grounded
- LED drivers shall be installed inside electrical enclosures
- 18 AWG 600V/I05C tinned stranded copper lead-wires are required for installation



\*AC Electronics/AC LED Power Designs warrants to the purchaser that each LED Driver will be free from defects in material or workmanship for a period of 5 years when operated at max case temp of up to <75°C; 3 years from date of manufacture when operated at a max case temp of up to 90°C when properly installed and under normal conditions of use. See aceleds.com for complete warranty policy.

3401 Avenue D, Arlington, TX 76011 • 800-375-6355 • www.aceleds.com

Data is based upon tests performed by AC Electronics in a controlled environment and representative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice. All specifications are nominal unless otherwise noted.



**Phone Instructions**


First you must have a Android device (phone/tablet) with NFC-V app downloaded.  
Open App; then place the device on top of the driver matching up sensors until it syncs up  
Basic format  
Write  
Insert the appropriate code from chart above  
Write  
Successfully written will appear



To Check: Read  
Read  
Shows you the Block - 00 00 00 00  
This is where the code you input appears

**IOUT/VOUT CURVE**

Use with NFC-V Reader App Available Free at Google App Store




**CONTROL THE IOUT WITH THE PROGRAMMING WAND. DOWNLOAD SOFTWARE FROM <http://www.aceleds.com/products-programmable.php>**

3401 Avenue D, Arlington, TX 76011 • 800-375-6355 • [www.aceleds.com](http://www.aceleds.com)

Data is based upon tests performed by AC Electronics in a controlled environment and representative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice. All specifications are nominal unless otherwise noted.


**Performance Characteristics**

**Life Time v.s. Case Temperature Curve**



**Derating Curve**

120Vac & 277Vac




3401 Avenue D, Arlington, TX 76011 • 800-375-6355 • www.aceleds.com


Data is based upon tests performed by AC Electronics in a controlled environment and representative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice. All specifications are nominal unless otherwise noted.

**Performance Characteristics**

**Efficiency v.s. Load**



**Power Factor v.s. Load**




3401 Avenue D, Arlington, TX 76011 • 800-375-6355 • www.aceleds.com


Data is based upon tests performed by AC Electronics in a controlled environment and representative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice. All specifications are nominal unless otherwise noted.

**Performance Characteristics**

**Output Current v.s. Dimming**



**Output Current v.s. Resistance**



3401 Avenue D, Arlington, TX 76011 • 800-375-6355 • www.aceleds.com

Data is based upon tests performed by AC Electronics in a controlled environment and representative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice. All specifications are nominal unless otherwise noted.