


MULTI-CURRENT SWITCHING AND DIMMING

ELECTRICAL SPECIFICATIONS:



Output Power Max.	Input Power	Input Current	Min PF (full load)	Max. THD (full load)	Output Voltage	Output Current	T case Max.	Min Start-Temp.	Efficiency Up To	IP Rating	Dimming Protocol	Dimming Range
43W	55-56W	0.47A @ 120V 0.2A @ 277V	>0.9	<20%	16-24V	1800mA±5%	90° C	-40° C	78%	64	0 to 10V	10 to 100%
34W	44W	0.36A @ 120V 0.12A @ 277V	>0.9	<20%	16-24V	1400mA±5%	90° C	-40° C	77%	64	0 to 10V	10 to 100%
25W	33W	0.28A @ 120V 0.12A @ 277V	>0.9	<20%	16-24V	1050mA±5%	90° C	-40° C	77%	64	0 to 10V	10 to 100%

WIRING:



Lead Lengths	Purple	5.9"	Gray	5.9"	
Black	5.9"	Blue	5.9"	Yellow	5.9"
White	5.9"	Red	5.9"	Brown	5.9"

PHYSICAL:



Dimensions

Length	5.3"
Width	2.9"
Height	1.18"
Weight	lbs.
Case Qty.	pcs.

SAFETY & PERFORMANCE:

- UL and cUL Recognized, Class 2
- UL Outdoor Type I
- Class A sound rating
- No PCBs
- Overload Protection
- IP64
- Open/Short Circuit Protection
- LED driver has a life expectancy of 50,000 hours at Tcase of ≤75°C
- LED driver has a life expectancy of 100,000 hours at Tcase of ≤65°C
- Warranty: 5 yrs based on max case temp of <75°C; 3 yrs based on max case temp of 90°C*
- Input/Output Isolation
- FCC Title 47 CFR Part 15
- Surge Protection (3 Kv)

INSTALLATION:

- LED drivers shall be installed inside electrical enclosures
- 18 AWG 600V/105C tinned strand copper lead-wires are required for installation
- Max Remote installation distance is 18 ft
- LED driver cases should be grounded



*AC Electronics/AC LED Power Designs warrants to the purchaser that each LED Driver will be free from defects in material or workmanship for a period of 5 years when operated at max case temp of up to <75°C; 3 years from date of manufacture when operated at a max case temp of up to 90°C when properly installed and under normal conditions of use. See [aceleds.com](http://www.aceleds.com) for complete warranty policy.

3401 Avenue D, Arlington, TX 76011 • 800-375-6355 • www.aceleds.com

Data is based upon tests performed by AC Electronics in a controlled environment and representative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice. All specifications are nominal unless otherwise noted.

