

MULTI-CURRENT SWITCHING AND DIMMING


Model Number **AC-84CD2100ATNC**

Input Voltage: 120-277V
Input Frequency: 50/60Hz
Side Mount/Leads

ELECTRICAL SPECIFICATIONS:


Output Power Max.	Input Power	Input Current	Minimum PF (full load)	Max. THD (full load)	Output Voltage	Output Current	T case Max.	Minimum Starting Temp.	Efficiency Up To	IP Rating	Dimming Protocol	Dimming Range
84W	95W	0.79A @ 120V 0.3A @ 277V	>0.9	<20%	24-40V	2100mA±5%	90° C	-40° C	88%	64	0 to 10V	10 to 100%
70W	80W	0.67A @ 120V 0.29A @ 277V	>0.9	<20%	24-40V	1750mA±5%	90° C	-40° C	87%	64	0 to 10V	10 to 100%
56W	65W	0.54A @ 120V 0.24A @ 277V	>0.9	<20%	24-40V	1400mA±5%	90° C	-40° C	86%	64	0 to 10V	10 to 100%

WIRING:



Lead Lengths						
Black	5.9"	Blue	5.9"	Purple	5.9"	Green
White	5.9"	Red	5.9"	Gray	5.9"	5.9"

PHYSICAL:



Dimensions	
Length	9.5"
Width	2.4"
Height	1.46"
Mounting	8.9"
Weight	xx lbs.
Case Qty.	xx pcs.

SAFETY & PERFORMANCE:

- UL and cUL Recognized
- Class 2
- UL Outdoor Type I
- Class A sound rating
- No PCBs
- IP64
- Open/Short Circuit Protection
- LED driver has a life expectancy of 50,000 hours at Tcase of ≤75°C
- LED driver has a life expectancy of 100,000 hours at Tcase of ≤65°C
- Warranty: 5 yrs based on max case temp of <75°C; 3 yrs based on max case temp of 90°C*
- Input/Output Isolation
- FCC Title 47 CFR Part 15
- Surge Protection (3 Kv)

INSTALLATION:

- LED drivers shall be installed inside electrical enclosures
- 18 AWG 600V/105C tinned strand copper lead-wires are required for installation
- Max Remote installation distance is 18 ft
- LED driver cases should be grounded



*AC Electronics/AC LED Power Designs warrants to the purchaser that each LED Driver will be free from defects in material or workmanship for a period of 5 years when operated at max case temp of up to <75°C; 3 years from date of manufacture when operated at a max case temp of up to 90°C when properly installed and under normal conditions of use. See aceleds.com for complete warranty policy.

3401 Avenue D, Arlington, TX 76011 • 800-375-6355 • www.aceleds.com

Data is based upon tests performed by AC Electronics in a controlled environment and representative performance. Actual performance can vary depending on operating conditions. Specifications are subject to change without notice. All specifications are nominal unless otherwise noted.

