

## ACE 2015 LED Driver List

Green: UL Approved												
Orange: UL Pending Submittal												
White: Designed no UL (Preliminary Specs only - No UL Submitted Yet)												
ACE Model Number	efficiency	pcs/ carton	carton size(cm)	Safety/Status/Date	Input Voltage	Output Type	Output Current	Output Voltage	PFC	Output Protection	L x W x H x M (in)	Warranty
CONSTANT CURRENT - PROGRAMMABLE DRIVERS												
AC-25CD1.25APME	82	40	29.4X27.6X19	UL/CUL Approved	120-277V	C.C.	350mA to 1250mA	15-55V	Yes	Open/Short/ Over Power protection	5.23" x 2.48" x 1.18" x 4.84"	5 yrs at 75°C Case Temp
AC25CD1.25APBME	82	40	30x28x25	UL/CUL Approved	120-277V	C.C.	350mA to 1250mA	15-55V	Yes	Open/Short/ Over Power protection	4.56 X 2.48 X 1.18	5 yrs at 75°C Case Temp
AC-25CD1.25APBUM	82			UL/CUL Approved	120-277V	C.C. 0-10 Dim	350mA to 1250mA	11-55V	Yes	Open/Short/ Over Power protection	4.56 X 2.48 X 1.18	5 yrs at 75°C Case Temp
AC-25CD1.25APMV	82	40	36x26x11		120-277V	C.C.	350mA to 1250mA	15-55V	Yes	Open/Short/ Over Power protection	6.22"x1.73"x1.22"x5.86"	5 yrs at 75°C Case Temp
AC-25CD1.25APUM	82			UL/CUL Approved	120-277V	C.C. 0-10 Dim	350mA to 1250mA	11-55V	Yes	Open/Short/ Over Power protection	5.23 x 2.48 x 1.18 x 4.84	5 yrs at 75°C Case Temp
AC-25CD1.25APUN	82			UL/CUL Approved	120-277V	C.C. 0-10 Dim	350mA to 1250mA	11-55V	Yes	Open/Short/ Over Power protection	6.22 x 1.73 x 1.22 x 5.86	5 yrs at 75°C Case Temp
AC-25CD1.25BPME	82			UL/CUL Approved	347V	C.C.	350mA to 1250mA	15-55V	Yes	Open/Short/ Over Power protection	5.23 x 2.48 x 1.18 x 4.84	5 yrs at 75°C Case Temp
AC-25CD1.25BPMV	82			UL/CUL Approved	347V	C.C.	350mA to 1250mA	15-55V	Yes	Open/Short/ Over Power protection	6.22 x 1.73 x 1.22 x 5.86	5 yrs at 75°C Case Temp
AC25CD1.25BPBME	82			UL/CUL Approved	347V	C.C.	350mA to 1250mA	15-55V	Yes	Open/Short/ Over Power protection	4.56 X 2.48 X 1.18	5 yrs at 75°C Case Temp
AC-30CD1.25APUP	82				120-277V	C.C. 0-10V Dim.	350mA to 1250mA	15-55V	Yes	Open/Short/ Over Power protection	12.4 x 1.3 x 1.08 x 11.8	5 yrs at 75°C Case Temp
AC-40CD1.4APKV	85	40	29.4X27.6X19	UL/CUL Approved	120-277V	C.C.	400mA to 1400mA	15-55V	Yes	Open/Short/ Over Power protection	5.23" x 2.48" x 1.18" x 4.84"	5 yrs at 75°C Case Temp
AC-40CD1.4APBKV	85	40	30x28x25	UL/CUL Approved	120-277V	C.C.	400mA to 1400mA	15-55V	Yes	Open/Short/ Over Power protection	4.56 X 2.48 X 1.18	5 yrs at 75°C Case Temp
AC-40CD1.4APMZ	85	40	36x26x11	UL Class 2 CSA LVLE	120-277V	C.C.	400mA to 1400mA	15-55V	Yes	Open/Short/ Over Power protection	6.22"x1.73"x1.22"x5.86"	5 yrs at 75°C Case Temp
AC-40CD1.4BPKV	85			UL Class 2 CSA LVLE	347V	C.C.	400mA to 1400mA	15-55V	Yes	Open/Short/ Over Power protection	5.23 x 2.48 x 1.18 x 4.84	5 yrs at 75°C Case Temp







CONSTANT CURRENT SERIES NON PROGRAMMABLE/ SWITCHABLE												
AC-23CD1.15UVTS	83	20	42x25x13	UL/cUL Approved Class 2	120-277V	C.C. 0-10V Dim. 3 Switch Current	1150/875/700mA	14-20	Yes	Open/Short/ Over Power protection	6.22"x1.73"x1.22"x5.86"	5 yrs at 75°C Case Temp
AC-23CD670AKQ	83.9	40	30x28x25	Multiple listing with AN-AC700S24WH	120-277V	C.C. 0-10V Dim.	670mA	20-34V	Yes	Open/Short/ Over Power protection	5" x 2.48" x 1.18" x 4.84"	5 yrs at 75°C Case Temp
AC-24C700UVH	83.9	50	30x28x25	UL Approved	120-277V	C.C.	700mA	18-36V	Yes	Open/Short/ Over Power protection	5" x 2.48" x 1.18" x 4.44"	5 yrs at 75°C Case Temp
AC-24CD700AKN	83.9	40	30X28X25	Multiple listing with AN-AC700S24WH	120-277	C.C. 0-10V Dim.	700mA	20-34V	Yes	Open/Short/ Over Power protection	5" x 2.48" x 1.18" x 4.84"	5 yrs at 75°C Case Temp
AC-24C700UVBMH	83.9	40	30x28x25	UL Approved	120-277V	C.C.	700mA	18-36V	Yes	Open/Short/ Over Power protection	5" x 2.48" x 1.18" x 4.44"	5 yrs at 75°C Case Temp
AC-24C1050UVH	81.7	50	30x28x25	UL/cUL Approved	120-277V	C.C.	1050mA	12-24V	Yes	Open/Short/ Over Power protection	5" x 2.48" x 1.18" x 4.44"	5 yrs at 75°C Case Temp
AC25CD1.05ATEAR	80	30	35.5X24.6X25.8	UL/cUL Approved Class 2	120-277V	C.C.	1050mA/900mA/750mA	16-24V	Yes	Open/Short/ Over Power protection	4.56"x2.48"x1.18"	5 yrs at 75°C Case Temp
AC-25CD700AQS	83				120/277V	C.C. 0-10 Dim	700mA+/-5%	22-36V	Yes	Open/Short/ Over Power protection	6.5" x 2.9" x 1.18" x 5.9"	5 yrs at 75°C Case Temp
AC-25CD700AUZ	83				120-277V	C.C. 0-10 Dim	700mA	22-36V	Yes	Open/Short/ Over Power protection	5 x 2.36 x 1.02 x 4.62	5 yrs at 75°C Case Temp
AC-25CD700ATM	83			UL, cUL Approved	120-277V	C.C. 0-10 Dim	700mA	22-36V	Yes	Open/Short/ Over Power protection	5.23 x 2.48 x 1.18 x 4.84	5 yrs at 75°C Case Temp
AC-26CD1.75ATS	80				120-277V	C.C. 0-10 Dim	1750mA	10-16V		Open/Short/ Over Power protection	6.22 x 1.73 x 1.22 x 5.86	5 yrs at 75°C Case Temp
AC-29CD800ALS	83	30	35.5x24.5x20	Multiple listing with AC950S40D-D4	120-277V	C.C. 0-10 Dim	800mA	28-36V	Yes	Open/Short/ Over Power protection	6.5" x 2.9" x 1.18" x 5.9"	5 yrs at 75°C Case Temp
AC-29CD800ANG	83	30	33x27x21		120-277V	C.C. 0-10V Dim.	800mA	22-36V	Yes	Open/Short/ Over Power protection	9.5"x1.7"x1.14"x8.9"	5 yrs at 75°C Case Temp
AC-29CD950AQBKP	90	20	42x25x13	Multiple listing with AC1050S32D-D3BM	120-277V	C.C. 0-10 Dim 4 Switch	950mA/900mA/700mA/500mA	10-30V	Yes	Open/Short/ Over Power protection	4.37"x3.07"x1.26"x4.02"	5 yrs at 75°C Case Temp
AC-30C700UV		50	35x27.5x21		120-277V	C.C.	700mA		Yes	Open/Short/ Over Power protection	5" x 2.48" x 1.18" x 3.16"	5 yrs at 75°C Case Temp
AC-30CD700AHD	80	50	37x27x26		120-277V	C.C.	700mA	28-42V	Yes	Open/Short/ Over Power protection	5.9"x 1.73" x 1.18" x 5.55"	5 yrs at 75°C Case Temp
AC-30C833ABPP	80	20	42x25x13		120-277V	C.C.	833mA	25-36V	Yes	Open/Short/ Over Power protection	4.37"x3.07"x1.26"x4.02"	5 yrs at 75°C Case Temp
AC-30C833UV	80	50	30x28x25	UL/cUL Approved Class 2	120-277V	C.C.	833mA	25-36V	Yes	Open/Short/ Over Power protection	5" x 2.48" x 1.18" x 3.16"	5 yrs at 75°C Case Temp
AC-30C833UV												















CONSTANT CURRENT SERIES NON PROGRAMMABLE/SWITCHABLE												
AC-98CD2.45AQPV	88	20	37x27x26	UL Class 2 CSA LVLE	120-277V	C.C. 0-10V Dim.	450mA/2100mA/1750mA/1400mA	24-40V	Yes	Open/Short/Over Power protection	9.5" x 2.4" x 1.46" x 8.9"	5 yrs at 75°C Case Temp
AC-98CD2.45AQBPV					120-277V	C.C. 0-10V Dim.	450mA/2100mA/1750mA/1400mA	24-40V	Yes	Open/Short/Over Power protection	9.5" x 2.4" x 1.46" x 8.9"	5 yrs at 75°C Case Temp
AC-98CD2.45AQR	90				120-277v	C.C. 0-10V Dim.	2450mA +/-5%	32-40V		Open/Short/Over Power protection	9.5" x 2.4" x 1.46" x 8.9"	5 yrs at 75°C Case Temp
AC-100CD350UV	88	20	37x27x26		120-277V	C.C. 0-10V Dim.	350mA	193-286V	Yes	Open/Short/Over Power protection	9.5" x 2.4" x 1.46" x 8.9"	5 yrs at 75°C Case Temp
AC-100CD700UVH	89	20	37x27x26	UL, CUL Approved	120-277V	C.C. 0-10V Dim.	700mA	86-143V	Yes	Open/Short/Over Power protection	9.5"x2.4"x1.46"x8.9"	5 yrs at 75°C Case Temp
AC-108CD2.0ATKS	88	20	37x27x26	Multiple listing with AC2100S150D-D3	120-277	C.C. 0-10V Dim. 3 Switch Current	2000mA/1700mA/1050mA	32-54V	Yes	Open/Short/Over Power protection	9.5"x2.4"x1.46"x8.9"	5 yrs at 75°C Case Temp
AC-108CD3.0ATR	88				120-277V	C.C. 0-10V Dim.	3000mA	22-36V	Yes	Open/Short/Over Power protection	6.85 x 3.58 x 1.73 x 6.42	5 yrs at 75°C Case Temp
AC-115CD1.2ACA	89	20	37x27x26	UL, CUL Approved	120-277	C.C. 0-10V Dim.	1200mA	70-96V	Yes	Open/Short/Over Power protection	9.5"x2.4"x1.46"x8.9"	5 yrs at 75°C Case Temp
AC-117CD3.0AUF	88				120-277V	C.C. 0-10V Dim.	3000mA	24-39V	Yes	Open/Short/Over Power protection	6.85 x 3.58 x 1.73 x 6.42	5 yrs at 75°C Case Temp
AC-144CD4.0ALM		10	39x27x11		120-277V	C.C.	4000mA	22-36V	Yes	Open/Short/Over Power protection	9.5"x2.64"x1.6"x8.9"	5 yrs at 75°C Case Temp
AC-150CD350AQQ	90				120-277V	C.C. 0-10V Dim.	350mA +/-5%	260-428V		Open/Short/Over Power protection	9.5"x2.64"x1.6"x8.9"	5 yrs at 75°C Case Temp
AC-150CD700UVTS									Yes	Open/Short/Over Power protection		5 yrs at 75°C Case Temp
	90	10	39x27x11	UL, CUL Approved	120-277	C.C. 0-10V Dim. 3 Switch Current	700/530/350mA	130-214V			9.5"x2.64"x1.6"x8.9"	5 yrs at 75°C Case Temp
AC-150CD700ATKX											9.5"x2.64"x1.6"x8.9"	5 yrs at 75°C Case Temp
AC-150CD700APE	90	10	39x27x11	UL, CUL Approved	120-277V	C.C. 0-10V Dim.	700mA	190-214V	Yes	Open/Short/Over Power protection	9.5"x2.64"x1.6"x8.9"	5 yrs at 75°C Case Temp
AC-150CD1.3AAY	89	10	39x27x11	UL, CUL Approved	120-277V	C.C.	1300mA	69-115V	Yes	Open/Short/Over Power protection	9.5"x2.64"x1.6"x8.9"	5 yrs at 75°C Case Temp
AC-150CD1.3APL	90	10	39x27x11	UL, CUL Approved	120-277V	C.C.	1300mA	104-115V	Yes	Open/Short/Over Power protection	9.5"x2.64"x1.6"x8.9"	5 yrs at 75°C Case Temp

CONSTANT CURRENT SERIES NON PROGRAMMABLE/SWITCHABLE												
AC-150CD1.4ALH	90	10	39x27x11		120-277V	C.C	1400mA	64-107V	Yes	Open/Short/ Over Power protection	9.5"x2.64"x1.6"x8.9"	5 yrs at 75°C Case Temp
AC-150CD1.5ABZ	89	10	39x27x11	UL, CUL Approved	120-277V	C.C	1500mA	60-100V	yes	Open/Short/ Over Power protection	9.5"x2.64"x1.6"x8.9"	5 yrs at 75°C Case Temp
AC-150CD1.05ARN	90			UL, CUL Approved	120-277V	C.C. 0-10V Dim.	1050mA	86-142V	Yes	Open/Short/ Over Power protection	9.5 x 2.4 x 1.46 x 8.9	5 yrs at 75°C Case Temp
AC-150CD2.1ATDD	89	10	39x27x11	UL, CUL Approved	120-277V	C.C.	2100mA	43-71V	Yes	Open/Short/ Over Power protection	9.5"x2.64"x1.6"x8.9"	5 yrs at 75°C Case Temp
AC-150CD2.0ATTC	87				120-277V	C.C. 0-10V Dim. 3 Switch	2000mA	45-75V	Yes	Open/Short/ Over Power protection	9.5"x2.64"x1.6"x8.9"	5 yrs at 75°C Case Temp
	86				120-277V	C.C. 0-10V Dim. 3 Switch	1600mA	45-75V	Yes	Open/Short/ Over Power protection	9.5"x2.64"x1.6"x8.9"	5 yrs at 75°C Case Temp
	85				120-277V	C.C. 0-10V Dim. 3 Switch	1400mA	45-75V	Yes	Open/Short/ Over Power protection	9.5"x2.64"x1.6"x8.9"	5 yrs at 75°C Case Temp
AC-150C3.0AQUL	87-90				120-277V	C.C. 0-10V Dim. 4 Switch	000mA/2500mA/2000mA/1000m	30-50V	Yes	Open/Short/ Over Power protection	9.5 x 2.4 x 1.46 x 8.9	5 yrs at 75°C Case Temp
AC-150C3.0UVTS	89	10	39x27x11	UL, CUL Approved	120-277V	C.C.	3000mA, 2000mA, 1000mA	30-50V	Yes	Open/Short/ Over Power protection	9.5"x2.64"x1.6"x8.9"	5 yrs at 75°C Case Temp
AC-150CD3.0AQQT	87				120/277V	C.C. 0-10V Dim. 4 Switch	3000mA, 2800mA, 2100mA, 1400mA	30-50V		Open/Short/ Over Power protection	9.5"x2.64"x1.6"x8.9"	5 yrs at 75°C Case Temp
AC-150CD3.0UVTS	89	10	39x27x11	UL, CUL Approved	120-277V	C.C.	3000mA, 2000mA, 1000mA	30-50V	Yes	Open/Short/ Over Power protection	9.5"x2.64"x1.6"x8.9"	5 yrs at 75°C Case Temp
AC-154CD700AVN	90				120-277V	C.C. 0-10V Dim.	700mA	132-220V	Yes	Open/Short/ Over Power protection	9.5 x 2.6 x 1.6 x 8.9	5 yrs at 75°C Case Temp
AC-200CD1.4AUU	93				120-277V	C.C. 0-10V Dim.	1400mA	71-142V	Yes	Open/Short/ Over Power protection	9.5 x 2.64 x 1.6 x 8.9	5 yrs at 75°C Case Temp
AC-200CD1.05AUT	93				120-277V	C.C. 0-10V Dim.	1050mA	95-190V	Yes	Open/Short/ Over Power protection	9.5 x 2.64 x 1.6 x 8.9	5 yrs at 75°C Case Temp
AC-200CD1.0APZ	93				120-277V	C.C. 0-10V Dim.	1000mA	90-200V	Yes	Open/Short/ Over Power protection	9.5"x2.64"x1.6"x8.9"	5 yrs at 75°C Case Temp
OCCUPANCY SENSOR SERIES												
AC-21CD510AGV (without RJ45)	80	40	30x28x25	UL Class 2 CSA LVLE	120-277V	C.C. 0-10V Dim.	510mA	25-41V	Yes	Open/Short/ Over Power protection	5.23"X2.48"X1.18"X4.84"	5 yrs at 75°C Case Temp
AC-21CD510TDC (with RJ45)	80	40	30x28x25	UL Class 2 CSA LVLE	120-277V	C.C. 0-10V Dim.	510mA	25-41V	Yes	Open/Short/ Over Power protection	5.23"X2.48"X1.18"X4.84"	5 yrs at 75°C Case Temp
AC-25CD620ATKL (with RJ45)	80	40	30x28x25	UL Class 2 CSA LVLE	120-277V	C.C. 0-10V Dim. 3 Switch	620mA/510mA/310mA	25-42V	Yes	Open/Short/ Over Power protection	5.23"X2.48"X1.18"X4.84"	5 yrs at 75°C Case Temp

## OCCUPANCY SENSOR SERIES

AC-42CD1.02AGU (without RJ45)	80	30	33x27x28	UL Class 2 CSA LVLE	120-277V	C.C.	1020mA	25-42V	Yes	Open/Short/Over Power protection	9.5" x 1.7" x 1.14" x 8.9"	5 yrs at 75°C Case Temp
AC-42CD1.02ATGH (with RJ45)	80	30	33x27x28	UL Class 2 CSA LVLE	120-277V	C.C.	1020mA	25-42V	Yes	Open/Short/Over Power protection	9.5" x 1.7" x 1.14" x 8.9"	5 yrs at 75°C Case Temp

## CONSTANT CURRENT - RESISTOR SET DRIVERS

AC-D40C1.1ARDN	86	30	35.5x24.5x20	UL Class 2 CSA LVLE CE Type TL	120-277V	C.C.	1100mA	28-36V	Yes	Open/Short/Over Power protection	12.4"X1.3"X1.1"X11.8"	5 yrs at 75°C Case Temp
AC-40CD1.1BRLZ	84	30	35.5x24.5x20	UL Class 2 CSA LVLE CE Type TL	347V	C.C. 0-10V Dim.	1100mA	28-36V	Yes	Open/Short/Over Power protection	12.4" x 1.3" x 1.1" x 11.8"	5 yrs at 75°C Case Temp
AC-D54C1.5ARDM	86	30	35.5x24.5x20	UL Class 2 CSA LVLE CE Type TL	120-277V	C.C.	1500mA	28-36V	Yes	Open/Short/Over Power protection	12.4"X1.3"X1.1"X11.8"	5 yrs at 75°C Case Temp
AC-54CD1.5ARNT	86	30	35.5x24.5x20	UL Class 2 CSA LVLE CE Type TL	120-277V	C.C. 0-10V Dim.	1500mA	28-36V	Yes	Open/Short/Over Power protection	12.4"X1.3"X1.1"X11.8"	5 yrs at 75°C Case Temp
AC-54CD1.5BRMA	84	30	35.5x24.5x20	UL Class 2 CSA LVLE CE Type TL	347V	C.C. 0-10V Dim.	1500mA	28-36V	Yes	Open/Short/Over Power protection	12.4" x 1.3" x 1.1" x 11.8"	5 yrs at 75°C Case Temp
AC-65CD1.75AMG	88	30	43x27x20	UL Class 2 CSA LVLE CE Type TL	120-277V	C.C.	1750mA	28-36V	Yes	Open/Short/Over Power protection	15.55"X1.49"X1.06"X15.23"	5 yrs at 75°C Case Temp
AC-D80C2.2ARDL	86	30	43x27x20	UL Class 2 CSA LVLE CE	120-277V	C.C.	2200mA	28-36V	Yes	Open/Short/Over Power protection	15.55"X1.49"X1.06"X15.23"	5 yrs at 75°C Case Temp
AC-80CD2.2BRMD	88	30	43x27x20	UL Class 2 CSA LVLE CE Type TL	347V	C.C.	2200mA	28-36V	Yes	Open/Short/Over Power protection	15.55"X1.49"X1.06"X15.23"	5 yrs at 75°C Case Temp

## CONSTANT CURRENT - TRIAC-DIMMING DRIVERS

AC-10CT700ATW	80				100-120V	C.C. Triac Dimming	700mA	10-14V	Yes	Open/Short/Over Power protection	3.86 x 1.46 x 1.04 x 3.7	5 yrs at 75°C Case Temp
AC-11CT440KRY	82				100-120V	C.C. Triac Dimming	440mA	18-25V	Yes	Open/Short/Over Power protection	4.33 x 1.77 x 1.1 x 4.1	5 yrs at 75°C Case Temp
AC-12CT350ABSY	83				100-120V	C.C. Triac Dimming	350mA	20-34V	Yes	Open/Short/Over Power protection	4.56 x 2.48 x 1.18	5 yrs at 75°C Case Temp
AC-15CT1.05ATX	80				100-120V	C.C. Triac Dimming	1050mA	10-14V	Yes	Open/Short/Over Power protection	3.86 x 1.46 x 1.04 x 3.7	5 yrs at 75°C Case Temp
AC-15CT350AFS	83				100-120V	C.C. Triac Dimming	350mA	29-42V	Yes	Open/Short/Over Power protection	3.86 x 1.46 x 1.04 x 3.7	5 yrs at 75°C Case Temp
AC-15CT700AFV	83				100-120V	C.C. Triac Dimming	700mA	15-21V	Yes	Open/Short/Over Power protection	3.86 x 1.46 x 1.04 x 3.7	5 yrs at 75°C Case Temp
AC-16CT440KRZ	87				100-120V	C.C. Triac Dimming	440mA	25-36V	Yes	Open/Short/Over Power protection	4.33 x 1.77 x 1.1 x 4.1	5 yrs at 75°C Case Temp

## CONSTANT CURRENT - TRIAC-DIMMING DRIVERS

AC-18CT350AGZ	83				100-120V	C.C. Triac Dimming	350mA	33-50V	Yes	Open/Short/ Over Power protection	3.86 x 1.46 x 1.06 x 3.7	5 yrs at 75°C Case Temp
AC-18CT500ASX	83				100-120V	C.C. Triac Dimming	500mA	25-36V	Yes	Open/Short/ Over Power protection	3.86 x 1.46 x 1.06 x 3.7	5 yrs at 75°C Case Temp
AC-21CT350AFT	83				100-120V	C.C. Triac Dimming	350mA	42-60V	Yes	Open/Short/ Over Power protection	3.86 x 1.46 x 1.04 x 3.7	5 yrs at 75°C Case Temp
AC-25CT350AGK	83				100-120V	C.C. Triac Dimming	350mA	50-71V	Yes	Open/Short/ Over Power protection	3.86 x 1.46 x 1.06 x 3.7	5 yrs at 75°C Case Temp
AC-25CT500AFS	82				100-120V	C.C. Triac Dimming	500mA	35-50V	Yes	Open/Short/ Over Power protection	3.86 x 1.46 x 1.06 x 3.7	5 yrs at 75°C Case Temp
AC-25CT700AFR	82				100-120V	C.C. Triac Dimming	700mA	25-35V	Yes	Open/Short/ Over Power protection	3.86 x 1.46 x 1.06 x 3.7	5 yrs at 75°C Case Temp
AC-35CT700APT	83				100-120V	C.C. Triac Dimming	700mA	35-50V	Yes	Open/Short/ Over Power protection	4.33 x 1.77 x 1.1 x 4.1	5 yrs at 75°C Case Temp

## CONSTANT CURRENT - MULTI-OUTPUTS DRIVERS

AC-D12C350UVH	75	50	35x27.5x21	UL Class 2 CSA LVLE	120-277V	C.C.	350mA	18-36V	Yes	Open/Short/ Over Power protection	5" x 2.48" x 1.18" x 4.44"	5 yrs at 75°C Case Temp
AC-D12C350BHV	83	30	43x27x17	UL / CUL Class 2	347V	C.C.	350mA	20-34V	Yes	Open/Short/ Over Power protection	9.5" x 1.26" x 1.17" x 8.9"	5 yrs at 75°C Case Temp
AC-D12C500UVH	78.5	50	35x27.5x21	UL Class 2 CSA LVLE	120-277V	C.C.	500mA	12-24V	Yes	Open/Short/ Over Power protection	5" x 2.48" x 1.18" x 4.44"	5 yrs at 75°C Case Temp
AC-D12C700UVH	77	50	35x27.5x21	UL Class 2 CSA LVLE	120-277V	C.C.	700mA	9-18V	Yes	Open/Short/ Over Power protection	5" x 2.48" x 1.18" x 4.44"	5 yrs at 75°C Case Temp
AC-D18C350UVH	87	40	37x27x20	UL Class 2 CSA LVLE	120-277V	C.C.	350mA	54-62V	Yes	Open/Short/ Over Power protection	6.77" x 2.4" x 1.22" x 6.22"	5 yrs at 75°C Case Temp
AC-D13C700UVH	77	50	35x27.5x21	UL / CUL Class 2	120-277V	C.C.	700mA	9-19V	Yes	Open/Short/ Over Power protection	5.00"x2.48"x1.18"X3.16"	5 yrs at 75°C Case Temp
AC-D18C350UVH	87	40	37x27x20	UL Class 2 CSA LVLE	120-277V	C.C.	350mA	54-62V	Yes	Open/Short/ Over Power protection	6.77" x 2.4" x 1.22" x 6.22"	5 yrs at 75°C Case Temp
AC-D15CD440ARF	83				120-277V	C.C. 0-10V Dim.	440mA	21-35V		Open/Short/ Over Power protection	9.5"x1.7"x1.14"x8.9"	5 yrs at 75°C Case Temp
AC-D15CD450AHW	83	30	33x27x21	UL / CUL Class 2	120-277V	C.C.	450mA	20-33V	Yes	Open/Short/ Over Power protection	9.5"x1.7"x1.14"x8.9"	5 yrs at 75°C Case Temp
AC-D15CD450BHX	83	30	33x27x21	UL / CUL Class 2	347V	C.C.	450mA	28-36V	Yes	Open/Short/ Over Power protection	9.5" x 1.7" x 1.14" x 8.9"	5 yrs at 75°C Case Temp
AC-D22CD700UVDT	80	30	35.5x24.5x20	UL / CUL Class 2	120-277V	C.C. 0-10V Dim.	700mA	24-32V	Yes	Open/Short/ Over Power protection	12.8"X1.34"X1.14"X12.5"	5 yrs at 75°C Case Temp

**CONSTANT CURRENT - MULTI-OUTPUTS DRIVERS**

AC-D22CD700UV	80	30	35.5x24.5x20	UL / CUL Class 2	120-277V	C.C. 0-10V Dim.	700mA	24-32V	Yes	Open/Short/ Over Power protection	12.8"x1.34"x1.14"x12.5"	5 yrs at 75°C Case Temp
AC-D42CD1.05AFZ	83	20	37x27x20		120-277V	C.C. 0-10V Dim.	1050mA	24-40V	Yes	Open/Short/ Over Power protection	9.5"x2.4"x1.46"x8.9"	5 yrs at 75°C Case Temp
AC-D48CD1.05AGM	83	20	37x37x20	UL / CUL Class 2	120-277V	C.C.	1050mA	27-45V	Yes	Open/Short/ Over Power protection	9.5" x 2.4" x 1.46" x 8.9"	5 yrs at 75°C Case Temp
AC-D79CD350AVP	88				120-277V	C.C 0-10V Dim	350mA	135-225V	Yes	Open/Short/ Over Power protection	9.5 x 2.6 x 1.6 x 8.9	5 yrs at 75°C Case Temp
AC-D84CD2100AHK		25			120-277V	C.C 0-10V Dim	2100mA					
AC-D86CD2.4ANS	85				120-277V	C.C 0-10V Dim	2400mA	28-36V	Yes	Open/Short/ Over Power protection	15.55"x2.99"x1.14"x15.2"	5 yrs at 75°C Case Temp
AC-D128CD2.5AEN	86				120-277V	C.C 0-10V Dim	2500mA	31-51V	Yes	Open/Short/ Over Power protection	9.5"x4.8"x1.46"x8.9"	5 yrs at 75°C Case Temp
AC-H40CD1.05APM	83				120-277V	C.C 0-10V Dim	1050mA	34-38V	Yes	Open/Short/ Over Power protection	9.5"x3.75"x1.77"x8.9"	5 yrs at 75°C Case Temp
AC-Q15CD350UVH	85	20	37x27x26		120-277V	C.C	350mA	26-43V	Yes	Open/Short/ Over Power protection	9.5"x4.8"x1.46"x8.9"	5 yrs at 75°C Case Temp
AC-Q15CD440ARE	85				120-277V	C.C 0-10V Dim	440mA	20-33V		Open/Short/ Over Power protection	8.3' x 2.4" x 1.16"	5 yrs at 75°C Case Temp
ACQ40CD635ABTFX	85	10	51x28x13		120-277V	C.C 0-10V Dim	700mA	34-57V	Yes	Open/Short/ Over Power protection	9.49"x3.74"x1.77"x8.9"	5 yrs at 75°C Case Temp
AC-Q41CD350ASP	85				120-277V	C.C. 0-10V Dim	350mA	70-116V		Open/Short/ Over Power protection	9.5" x 3.75" x 1.77" x 8.9"	5 yrs at 75°C Case Temp
AC-T30CD700AKA	83	20	37x27x20	UL / CUL Class 2	120-277V	C.C.	700mA	25-42V	Yes	Open/Short/ Over Power protection	9.5"x2.4"x1.46"x8.9"	5 yrs at 75°C Case Temp
AC-T30CD700BKB	86	20	37x27x20	UL / CUL Class 2	347V	C.C	700mA	25-42V	Yes	Open/Short/ Over Power protection	9.5" x 2.4" x 1.46" x 8.9"	5 yrs at 75°C Case Temp
AC-T48CD1.05AGN	83	10	51x28x13	UL / CUL Class 2	120-277V	C.C.	1050mA	24-45V	Yes	Open/Short/ Over Power protection	9.5"x3.75"x1.77"x8.9"	5 yrs at 75°C Case Temp
AC-Q15CD450BHZ	85	20	37x27x20	UL / CUL Class 2	347V	C.C.	450mA	20-33V	Yes	Open/Short/ Over Power protection	10.2" x 2.4" x 1.46" x 9.7"	5 yrs at 75°C Case Temp
AC-Q21CD180ARX	85				120-277V	C.C. 0-10V Dim.	180mA	70-116V	Yes	Open/Short/ Over Power protection	9.5 x 2.4 x 1.46 x 8.9	5 yrs at 75°C Case Temp
AC-Q25C700UVH	83	10	51x28x13	UL / CUL Class 2	120-277V	C.C	700mA	21-36V	Yes	Open/Short/ Over Power protection	9.5"x3.75"x1.77"x8.9"	5 yrs at 75°C Case Temp
AC-Q25C700UVH	83	10	51x28x13	UL / CUL Class 2	120-277V	C.C	700mA	21-36V	Yes	Open/Short/ Over Power protection	9.5"x3.75"x1.77"x8.9"	5 yrs at 75°C Case Temp







**CONSTANT VOLTAGE**

AC-150VD36AEB		20	37x27x26	UL/cUL Approved Class 2	120-277V	C.V. 0-10V Dim.	4.2A	36V	Yes	Over Voltage/Short/ Over Power protection	9.5" x 2.4" x 1.6" x 8.9"	5 yrs at 75°C Case Temp
AC150VD48A3.1SR	90				120-277V	C.V. 0-10V Dim.	0.312A to 3.12A	48V	Yes	Over Voltage/Short/ Over Power protection	9.5" x 2.4" x 1.6" x 8.9"	5 yrs at 75°C Case Temp
AC-A150VD36H4.2	87	20	37x27x26	UL/cUL Approved Class 2	120-277V	C.V. 0-10V Dim.	4.2-5A	36V	Yes	Over Voltage/Short/ Over Power protection	9.5" x 2.4" x 1.6" x 8.9"	5 yrs at 75°C Case Temp