

Minuteman 5™

LED Retrofit Kit For Decorative Wall Pack

*"Fits Any Decorative Wall Pack Housing
2"H x 17"W x 7"D or Larger"*

LED Replacement Components for 150 Watt & 175 Watt HID Fixtures

Made In USA 




LED Retrofit Kit Model Number CDCW36/350/50X2

Fits Lighting Housings:
2"H x 17"W x 7"D or Larger

Kit Includes:

- Two-Output Channel, Class 2 LED Driver, Model Number: AC-D12C350UVH
- 2 PCB LED Arrays with 20 Cree XP-G2 LEDs mounted to industrial grade aluminum LED Driver bracket (10 Leds per array)
- Instructions for Installation
- All required assembly hardware

Wiring Diagram



Warranty

LED Retrofit Kit warranty is only valid when it is used in the 2"H x 17"W x 7"D or Larger lighting housing it was designed to be used in unless otherwise approved in writing by AC Electronics. Any other use in any other lighting housing or use with non-AC specified or supplied components will void this warranty.

*AC warrants to the purchaser that this LED Retrofit Kit will be free from defects in material or workmanship for a period of 5 years from date of manufacture, when operated at a maximum ambient temperature of 110°F or 45°C, when properly installed and under normal conditions of use.

The warranty excludes damage resulting from improper installation or damage caused by fire or severe weather conditions including, but not limited to, lightning and storms. Evidence of direct exposure to water on the failed units voids the warranty.

See www.aceleds.com for complete warranty policy.

Specifications

Item	Specification
Input Voltage	120-277V, 50/60 Hz
Fixture CRI	75
Fixture Color Temperature	4660
Fixture Lumens	2329
Fixture Efficacy	92.9 lumen per watt
Lumen Maintenance	≥70% @ 5 years
Zonal Lumen Performance	0-40° ≥37%; 40-70° ≥42%
Warranty	5 years*
LED Quantity (Brand: Cree XP-G2)	20
LED TMP Temperature @ 25°C	52.9°C
Input Power	25W
Driver Efficiency	75%
Power Factor @ 277V	0.967
THD @ 277V	2.2%
Driver TMP @ 25°C ambient	51.8°C
Noise	<24dB
EMI	FCC part 15
Max Operating Temperature	45°C Ambient
Min Operation Temperature	-40°C Ambient
LED Retrofit Kit Dimensions / Weight	2"H x 17"W x 7"D / 3 lbs.



Bodine ELI-100-SD Battery Backup Device

Approved For Use With AC LED Retrofit Kits

This device will operate 1 or 2 kits for a minimum of 90 minutes in the absence of main power.

- 120/277V, 60Hz, 100W Max Load
- 120W Input Power Rating

- Test Switch
- Charging Indicator Light
- Temperature Rating (Ambient) 68° F to 86° F (20° C to 30° C)
- Not included, available from Phillips



Tork® 2107 Photocell

Approved For Use With AC LED Retrofit Kits

- 120/277V 1800 VA Ballast Load
- 1 To 5 FC Turn On Light Level
- 3 To 15 FC Turn Off Light Level
- SPST Switch
- 16 AWG 6 Inch Wire Lead Terminal
- Temperature Rating -40 to 140°F
- 1/2" Conduit Mounting
- Not included, available from secondary sources



AC Electronics LED Retrofit Kit vs. Standard HID Lights

Wall Pack Light Source	Input Wattage	Lifespan Hrs/Yrs	Energy Use (24hrs/day) Annual	Annual Cost (maintenance + electricity) @ \$0.11/kWh	Electrical Cost Savings
HID	165	24,000/ 2.7	1446 kWh	\$159.00	
LED	25	50,000/ 5.7	219 kWh	\$24.09	85%

